THE KARAT 安裝说明书 INSTALLATION INSTRUCTIONS

NANA **VESSEL LAVATORY** 陶瓷台上盆 35379VN-WK

安装说明书 INSTALLATION INSTRUCTION

安装之前

- 有关安装属专业性质,故盥洗台下脸盆必须经由受过 训练及有经验的技师进行安装。
- 切勿在本品上使用胶黏剂或有黏性的密封胶。
- 检查出水及供水管道,如有需要便更换。
- 安装之前先开启新脸盆的包装,检查有无损毁后放回 纸箱中以免碰坏,到准备安装时才取用。
- 遵守当地所有给排水及建筑规定。

所需工具及物料

(不随货供应)

- 封边胶
- 炭笔
- 卷尺
- 尖刀或剪刀
- 匙孔线锯或手提电锯
- 钻(直径1/2英寸或更大的钻咀)
- 防护眼镜

尺寸图

单位:毫米 Unit:mm

- 锤子

• 抹布或抹手纸 注意: 若盥洗台的物料并非木或木质合成品,则你可能 需要在安装脸盆时使用其他更专门的工具。

BEFORE YOU BEGIN

- Due to the nature of the installation, undercounter lavatories should be installed by trained and experienced installers.
- Do not use adhesives or adhesive sealants with this product.
- Inspect the waste and supply tubing; replace if
- Prior to installation, unpack the new lavatory and inspect it for damage. Return the lavatory its protective carton until you are ready to install it.
- Observe all local plumbing and building codes.

TOOLS AND MATERIALS (Not Supplied)

- Sealant
- Pencil
- Tape measure
- Sharp knife or scissors
- Keyhole or saber saw
- Drill (1/2" dia. drill bit or larger)
- Safety glasses
- Hammer
- Rags or paper toweling

NOTE: You may require different, more specialized tools to install this lavatory to countertop materials other than wood or wood composites.

所有台面的安装

- 如还未安装盥洗台,请在这时装上。
- 按照龙头安装说明引钻龙头孔。
- 按照制造商的说明书,在盥洗台装上水龙头。 按照制造商的说明书,在脸盆下装上排水管。

注意: 请勿在本品上使用胶黏剂或有黏性的密封 胶。在与盥洗台接触的脸盆边缘,如珠串般滴上

- 在木、木质合成物及大理石的盥洗台上安装脸 盆时,可使用夹具及螺钉(配件不随货供应,用 户需自行购买)。其他物料制造的盥洗台,则请参考盥洗台制造商的说明书上的建议,使 用适当的扣件。
- 在上紧夹具前,先将脸盆平整地放在盥洗台切口下,然后小心将脸盆拉起直至合度才可上 夹具,切勿上得太紧。
- 立即擦去多余的密封胶。
- 最后将所有水管及水龙关与脸盆连接妥当,确 保安装乃符合水管及水龙头的一切有关的安装
- 使用非腐蚀性的清洁剂进行清洁。


FOR ALL **INSTALLATIONS**

sealants.

- If the countertop has not been installed, install it at this time.
- Drill the faucet holes according to the faucet installation instructions.
- Install the faucet to the countertop according to the manufacturer's instructions.
- Install the drain to the lavatory according to the manufacturer's instructions. **NOTE:** Do not use adhesives or adhesive
- Apply a continuous bead of quality sealant to the lavatory rim where it will contact the countertop.
- For wood, wood composite, and marble countertops, install the lavatory to the countertop with the clamps and screws (**Not Supplied**) . For other countertop materials, refer to the countertop manufacturer's instructions for recommended fasteners.
- Position the lavatory squarely under the cutout before tightening the clamps. Draw the lavatory rim up to the countertop until it is snug. Do not overtighten.
- Immediately wipe away any excess sealant. Make the final drain and faucet connection to complete the IMake the final drain and faucet
- connection to complete the lavatory installation. Be sure to follow all instructions packed with the drain and faucet.
- Clean up with a non-abrasive cleaner.

ROUGHING-IN

480






安装脸盆

确认购买的台上盆类型

- 根据台上盆的形状,确认台面开孔的尺寸; 无龙头孔需要在台面上确认开龙头孔尺寸。 注意:开孔尺寸的确认以台上盆底部能与 台面接触水平、紧密为准。
- 无孔龙头台上盆在台面上应预留安装龙头 的距离。
- 根据画出的开孔尺寸线,用切割机、电钻 等工具进行加工,并修饰孔的边缘。




- 安装去水器
- 在台上盆与台面接触的部位涂抹防水玻璃胶。 注意:只能使用柔软的玻璃胶,禁止使用环 氧树脂胶等。





- 待密封材料固化后,再安装龙头(无龙头孔台上
- 盆)和进排水连接管。 • 无龙头孔台上盆安装完成。





INSTALL THE LAVATORY

- Confirm the type of onstage basin purchased
- Confirm the size of the hole; the size shall be confirmed on the table. Note: The size of the opening is confirmed according to the contact level and tightness of the bottom of the basin on the table.
- The distance between the installation faucet should be reserved for the upper basin on the
- According to the drawn hole size line, with cutting machine, electric drill and other tools, and modify the edge of the hole.
- Install the water remover
- Apply waterproof glass glue to the contact between the basin and the table.
- Note: can only use soft glass glue, prohibit using epoxy resin glue, etc. After the sealing material is fixed, install the faucet (tap basin) and inlet and drainage connection pipe.
- The basin without tap platform is completed.

保养和清洁

为确保最佳使用效果,在保养您的产品时,请注意以下几

- 对整个产品使用任何清洁剂之前,请在产品不醒目处 试用。
- 使用清洁剂后,将表面擦拭干净,并用水彻底冲洗。 同时冲洗并擦干喷洒到附近表面的清洁剂。
- 勿使用清洁剂浸泡产品表面。
- 使用柔软的湿布或海绵。避免使用如刷子或百洁布之 类的磨损性材料擦洗产品表面。
- 避免让产品表面长时间接触退色性材料。
- 请于每次使用后彻底冲洗并擦干表面。

KOHLER ASIA PACIFIC LIMITED Address: 14/F, No. 88 Gloucester Road Wanchai, HongKong

CARE AND CLEANING

For best results, keep the following in mind when caring for your product:

- Always test your cleaning solution on an inconspicuous area before applying to the entire surface.
- Wipe surfaces clean and rinse completely with water immediately after applying cleaner. Rinse and dry any overspray that lands on nearby surfaces.
- Do not allow cleaners to soak on surfaces.
- Use a soft, dampened sponge or cloth. Never use an abrasive material such as a brush or scouring pad to clean surfaces.
- Be careful not to leave staining materials in contact with the surface for extended periods of time.
- The ideal cleaning technique is to rinse thoroughly and blot dry any water from the surface after each use.
- Connect the trap to the drain.
- Run water into the lavatory. Check all connections for leaks.