

INDUCTION CAULDRON SERIES

Mantru.e



800 Induction Cauldron

- Real-fire simulation technology. Heating uniformity and bigger heating area.
- 5-level power control;
- LED power display;

Model	ZC-C8020A / ZC-C8025A
Dimension(mm)	1100x1100x(810+440)
Rated Power(kw)	20 / 25
Rated Voltage	380V 3-phase 5-line



600 Induction Cauldron

Model	ZC-C6015A
Dimension(mm)	900x900x(810+440)
Rated Power(kw)	15
Rated Voltage	380V 3-phase 5-line



900 Induction Cauldron

Model	ZC-C9025A
Dimension(mm)	1100x1200x(810+440)
Rated Power(kw)	25
Rated Voltage	380V 3-phase 5-line



1000 Induction Cauldron

Model	ZC-C10025A / ZC-C10030A
Dimension(mm)	1300x1300x(810+440)
Rated Power(kw)	25 / 30
Rated Voltage	380V 3-phase 5-line



1200 Induction Cauldron

Model	ZC-C12030A
Dimension(mm)	1400x1500x(810+440)
Rated Power(kw)	30
Rated Voltage	380V 3-phase 5-line



Temperature-Control Induction Cauldron

Model	ZC-C8020A-DW / ZC-C8025A-DW
Dimension(mm)	1100x1100x(810+440)
Rated Power(kw)	20 / 25
Rated Voltage	380V 3-phase 5-line



800 Dual Induction Cauldron

Model	ZC2-C8040A / ZC2-C8050A
Dimension(mm)	2200x1100x(810+440)
Rated Power(kw)	20+20 / 25+25
Rated Voltage	380V 3-phase 5-line