



# PRODUCT DATA SHEET

## iL4





## PRODUCT DESCRIPTION

As small and handy as a pen but as rugged and most importantly as safe as other lamps in the iL series: The Ledlenser iL4. Designed specifically for environments where explosive atmospheres such as flammable gases, vapors or dust clouds can occur for a short period. And yet it's the cheapest lamp in the iL series. So not even costs will explode.

- Extremely lightweight (65 g incl. batteries)
- Extremely small and handy (L 14.0 cm)
- Battery operated, uses 2x alkaline AAA
- Suitable for use in environments with gas group IIA, B or C (up to T4) or dusts group IIIA, B or C (up to T135°C)



### TECHNICAL DATA

Length defocused [mm]	140
Length [mm]	140
Head diameter [mm]	20
Tube diameter [mm]	20
Weight incl. batteries [g]	65
Weight without batteries [g]	42
Focus function	No
Head material	PC
Tube material	PC
Optic	Plastic lense (PMMA)
Cartridge	No

### POWER SUPPLY

Power source type	Battery
Battery quantity	2
Battery type	Alkaline
Battery description	Micro (AAA) 1.5V
Rechargeable	No

### EXPLOSION PROTECTION

ATEX Certificate	Baseefa18ATEX0070
IEC Ex Certificate	IECEX BAS18.0008
Ex marking	II 3G Ex ic IIC T4 Gc II 3D Ex ic IIIC T135°C Dc
Ex-Zone Gas	2
Gas Group	IIA, IIB, IIC
Temperature Class Gas	T4
Ex-Zone Dust	22
Dust Group	IIIA, IIIB, IIIC
Temperature Class Dust	135 °C

### FURTHER SPECIFICATIONS

IP class	IP68
Drop test (drop height) [m]	1
Working temperature range [°C]	-20 to +40

### LIGHT FUNCTIONS

Power

### LIGHT SOURCE

Amount LEDs	1
LED type	Power LED
Color	White
Color temperature [K]	6000 to 7500
Color rendering index (CRI)	70

### LIGHT VALUES

	Boost	Power	Mid Power	Low Power
Light output <sup>1</sup> [lm]		80		
Beam distance <sup>1</sup> [m]		50		
Run time <sup>1</sup> [h]		4		

### SWITCH

End Cap Switch

# iL4

## PACKAGING AND LOGISTICS



### PACKAGING INFORMATION

Type of packaging	Sleeve Box
Scope of delivery	1 set of batteries
Item No.	500684
Customs tariff number	85131000
Color	black
MSRP price (€)	34.90

### SINGLE PACKAGE

Dimensions W x H x D [cm]	19 x 7 x 5.8
Gross weight [g]	155
GTIN-13	4058205000444

### INNER CARTON

Unit	6
Dimensions W x D x H [cm]	22.5 x 20 x 13
Gross weight [g]	1071.5
GTIN-13	4058205000468

### EXPORT CARTON

Unit	48
Dimensions W x D x H [cm]	47 x 25.5 x 45
Gross weight [kg]	9.55
GTIN-13	4058205000482

iL4

## ACCESSORIES

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME	MSRP
Fastenings / Brackets	500954	Helmet Mount Type A	19.90 €
Fastenings / Brackets	500955	Helmet Mount Type B	19.90 €
Fastenings / Brackets	500956	Intelligent Clip Type F	8.90 €
Battery	500981	4x AAA Alkaline Ionic	3.49 €



## PRODUCT SERIES

### The Ledlenser iL series

If you're working in explosive environments, safety is extremely important when it comes to electronics. Safety which is defined in the ATEX directives of the European Union. Lamps in the Ledlenser EX and iL series meet these standards in every respect. Designed specifically for contact with explosive gases, vapors and dust in the best possible groups IIC and IIIC. Featuring dust and water protection, and certified to ATEX and IECEx. Yet both lines - in accordance with the ATEX workplace directives - are designed for different types of explosion hazards. The EX-series is suitable for areas where explosive atmospheres are regularly present (zones 0, 1, 20 or 21) and the iL-series for Zone 2/22. So you'll find the perfect lamp for any environment.

## FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurements according to ANSI FL1 on the respective setting. Average values, in some cases, deviations by +/- 15 % may occur due to technical reasons. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If no setting is explicitly indicated, measurement is based on "energy saving mode."

4) Warranty period of five years from the date of purchase, seven years if the product is registered online on our website. The warranty is valid worldwide and legal warranty rights also apply. It covers defects in materials and workmanship. For the proper functioning of rechargeable batteries a different warranty period of 24 months applies. Excluded from this warranty are the products of the "Solidline" series, Ledlenser K1 and Ledlenser K2. The warranty does not apply to defects in batteries, holsters, pouches, remote switches, color filters, imprints or surface coatings. The guarantor is Ledlenser GmbH & Co. KG, Kronenstr. 5 - 7, 42699 Solingen, Germany. More information: [ledlenser.com/warranty](http://ledlenser.com/warranty)