

Todayt&c







Printing Quality

Rendition absolute Red

70.4 (a*值)



0° barcode



90° barcode




Min. printable characte




Graphics




Substrate Compatibility



Sensitivity





Resistance Test

Washing resistance

Placing the printed label in a washing machine with 4‰ soapy water at 40°C for 30 minutes.

Observing its print attenuation: OK



No Obvious Fading

Dry-cleaning resistance

Placing the printed label in a washing machine with CCL4 solution at 40°C for 30 minutes.

Observing its print attenuation: OK



No Obvious Fading

Ironing test

Placing the printed label under an ironing machine for 5 minutes.

OK Observing its print attenuation: OK

No Obvious Fading

Recommended Applications



Receipt and delivery labels for warehouses



Pre-packaging





Pharmaceuticals



Daily chemicals



Hot working



Retail label



Digital & electronics



Refrigeration

Clothing tags



Labels for automobile industry



Chemical industry



Nursery gardens and flowers



Production lines



Wooden products



Steel & iron manufacturing



Fixed assets

Garment and

accessories



Electrical equipment

Shoe tongues



equipment



Properties

PET film	Ribbon
Thickness: 4.5μm	Thickness: 6.2±1.0μm
Ink	
Color: red Melting point: 110±5°C	
Storage condition	
Temperature: 5~35°C Humidity: 20~80% Validity period: 12 months	

Product Comparison



Certifications and Permits









MSDS





HALOGEN HALOGEN

Compatible With

- Zebra

- Honeywell

- Datamax

- Avery

- Intermec

- TSC

- SATO

- Printronix

- other flat-head printings

Red Wash Care Resin Ribbon

BARCODING THE WORLD



Hangzhou Todaytec Digital Co., Ltd.

All product specifications can be found at our website www.todaytec.com/en/



(S) Marketing Department: +86 571-8577-1623



marketing@todaytec.com.cn

