


# DISPLAY CHILLER

- Blower System
- With Auto Door Lock System
- Heated Glass




1D/DC-S

1 Door



Top View




Front View




2D/DC-S

2 Door



Top View




Front View




3D/DC-S

3 Door



Top View



Front View

## HIGHLIGHTS

### Internally lighted promotes impulse sales.

Shielded fluorescent internal lighting assures safety.

### Illuminated

display signboard.

### Magnetic heated glass door

with self closing system, it can effectively prevent the loss of cool air.

### Door stationery opened,

makes it easy and convenient to put in and take out the goods.

### High-density Cyclo-isopentane Polyurethane

insulated body saves energy.

### Automatic defrost system

saves energy consumption and provide shortest possible defrost cycle.

Refrigeration system protected from corrosion by urethane-treated evaporator coil.

### Blower system (assisted with fan)

will ensure homogenous coolness in the storage space.

### Environmental friendly refrigerant

(CFC and HCFC Free) R134a.

### 5 tier removable and adjustable shelves.

### Self contained system,

no plumbing required.

### Tested at ambient temperature of 32°C,

with no load.

## TABLE INFO



	1 DOOR	2 DOOR	3 DOOR
MODEL	1D/DC-G 1D/DC-S	2D/DC-G 2D/DC-S	3D/DC-G 3D/DC-S
Temperature°C (celsius)	+2 to +8	+2 to +8	+2 to +8
External Dimension (mm)	635 x 710 x 2060	1260 x 710 x 2060	1880 x 710 x 2060
Internal Dimension (mm)	520 x 595 x 1435	1143 x 595 x 1435	1765 x 595 x 1435
Gross Volume (Litres)	444	976	1507
Voltage/ Frequency (V/ Hz)	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz
Weight (kgs)	95	157	209
Compressor	1/4Hp	2/5Hp	1/2Hp
Wattage (W)	700 - 770	950 - 1050	1080 - 1190
Ampere (A)	4.3 - 4.7	5.3 - 6.0	6.6 - 7.5
Energy Consumption (kw/ 24h)	4.5 - 5.00	6.5 - 7.00	11.8 - 12.00
System	Forced Convection	Forced Convection	Forced Convection
Refrigerant/ Grams	R134a / 360g	R134a / 460g	R134a / 460g
Defrost System	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation
Temperature Control	Digital	Digital	Digital
Shelves (PVC)	5 pcs per door	5 pcs per door	5 pcs per door
Number Of Clips	20	40	60
Unit For 20ft Container	27	12	9
Unit For 40ft Container	54	27	18

Note:

Colour of Door Frame : G - Gold Aluminium Frame /  
S - Silve Aluminium Frame

As product improvement is an on going process, we reserve the right to change specifications or design without notice.