# **HIGHLIGHTS**

#### Internally lighted promotes impulse sales.

Shielded fluorescent internal lighting assures safely.

#### Illuminated

display signboard.

# **High-density Cyclo-isopentane Polyurethance** insulated body saves energy.

#### Automatic defrost system

saves energy consumption and provide shortest possible defrost cycle.

#### Refrigeration system protected from corrosion

by urethane-treated evaporator coil.

#### Blower system (assisted with fan)

will ensure homogenous coolness in the storage space.

#### Magnetic

glass door.

#### Environmental friendly refrigerant (CFC and HCFC Free) R134a.

4 tier removable and adjustable shelves.

### Self contained system,

no plumbing required.

### Certified fan is used,

VDE & CE approved.

#### Tested at ambient temperature of 32°C,

with no load.

## TABLE INFO





MODEL	1D/MDC-G	1D/MDC-S
		·
Temperature°C (celsius)	+2 to +8	+2 to +8
External Dimension (mm)	590 x (580 + 50) x 1740	590 x (580 + 50) x 1740
Internal Dimension (mm)	495 x 680 x 1270	495 x 680 x 1270
Gross Volume (Litres)	302	302
Voltage/ Frequency (V/ Hz)	230V/1/50Hz	230V/1/50Hz
	220V/1/60Hz	220V/1/60Hz
Weight (kgs)	75	75
Compressor	1/6Hp	1/6Hp
Wattage (W)	340 - 380	340 - 380
Ampere (A)	2.2 - 2.4	2.2 - 2.4
Energy Consumption (kw/ 24h)	-	*
System	Forced Convection	Forced Convection
Refrigerant/ Grams	R134a / 270g	R134a / 270g
Defrost System	Forced Air Circulation	Forced Air Circulation
Temperature Control	Mechanical	Mechanical
Shelves (Pvc)	4 pcs per door	4 pcs per door
Number Of Clips	16	16
Unit For 20ft Container	27	27
Unit For 40ft Container	57	57

Colour of Door Frame : G - Gold Aluminium Frame /

S - Silve Aluminium Frame

As product improvement is an on going process, we reserve the right to change specifications or design without notice.

