

# RECTANGULAR CONFECTIONERY SHOWCASE - LAMINATED BASE

- Blower System
- Double Glass




RCS 12SB13-3FB




RCS 12GM13-2FB


2 Tiers




3 Tiers





Back View



Front View



Side View



## HIGHLIGHTS

### Maroon (GM) or Black (SB)

Vinyl laminated base.

### Suitable for cake and confectionery.

An ideal showcase, which creates impulse sales.

### Display compartment is constructed

with double layer hardened glass.

### 4 sides clear glass with front rectangular glass

and internal lighting for excellent display.

### Temperature of entire glass case is even,

ensure by forced by air circulation.

### Automatic defrost system

saves energy consumption and provide shortest possible defrost cycle.

### Refrigeration system protected from corrosion

by urethane-treated evaporator coil.

### Blower system (assisted with fan)

will ensure homogenous coolness in the storage space.

### Oversized coil and low velocity fan system

maintain high humidity and low temperature and product freshness.

### Environmental friendly refrigerant

(CFC and HCFC Free) R134a.

### 2/3 tier removable and adjustable shelves.

### Interior lighting,

shielded fluorescent interior lighting assures safety.

### White base glass shelves, for easier cleaning

and comply with sanitation requirement. White base enhance eye catching display.

### Tested at ambient temperature of 32°C,

with no load.

## TABLE INFO

MEPS  
Australia

MODEL	- 2 Tier	RCS 09SB13-2FB RCS 09GM13-2FB	RCS 12SB13-2FB RCS 12GM13-2FB	RCS 15SB13-2FB RCS 15GM13-2FB	RCS 18SB13-2FB RCS 18GM13-2FB	RCS 24SB13-2FB RCS 24GM13-2FB
	- 3 Tier	RCS 09SB13-3FB RCS 09GM13-3FB	RCS 12SB13-3FB RCS 12GM13-3FB	RCS 15SB13-3FB RCS 15GM13-3FB	RCS 18SB13-3FB RCS 18GM13-3FB	RCS 24SB13-3FB RCS 24GM13-3FB
Temperature°C (celsius)		+2 to +8	+2 to +8	+2 to +8	+2 to +8	+2 to +8
External Dimension (mm)		900 x 700 x 1350	1200 x 700 x 1350	1500 x 700 x 1350	1800 x 700 x 1350	2400 x 700 x 1350
Internal Dimension (mm)		780 x 580 x 700	1080 x 580 x 700	1380 x 580 x 700	1680 x 580 x 700	2280 x 580 x 700
External Finishing		Stainless Steel Laminated Steel Sheet	Stainless Steel Laminated Steel Sheet	Stainless Steel Laminated Steel Sheet	Stainless Steel Laminated Steel Sheet	Stainless Steel Laminated Steel Sheet
Internal Finishing		Stainless Steel Aluminium	Stainless Steel Aluminium	Stainless Steel Aluminium	Stainless Steel Aluminium	Stainless Steel Aluminium
Voltage/ Frequency (V/Hz)		230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz
Weight (kgs)		211	245	280	331	425
Cooling Capacity (W)		646	913	1002	1346	1628
Wattage (W)		760 - 840	950 - 1050	1045 - 1155	1330 - 1470	1615 - 1785
Ampere (A)		4.75 - 5.25	5.7 - 6.3	5.9 - 6.3	7.6 - 8.4	9.0 - 10.0
Energy Consumption (kw/ 24h)		16.6 - 18.4	18.9 - 20.9	21.7 - 23.9	24.4 - 27.0	31.1 - 34.3
Condenser		Air Cooled	Air Cooled	Air Cooled	Air Cooled	Air Cooled
System		Force Convection	Force Convection	Force Convection	Force Convection	Force Convection
Refrigerant/ Grams		R134a / 400g	R134a / 560g	R134a / 690g	R134a / 800g	R134a / 900g
Defrost System		Forced Air Circulation	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation
Temperature Control		Digital	Digital	Digital	Digital	Digital
Glass Shelves (Levels)		2	2	2	2	2
Gross Volume (Litres)		370	500	630	770	1030
Unit For 20ft Container		14	11	10	7	4
Unit For 40ft Container		30	24	22	16	8

Optional: To include key lock, prevents unauthorised access to the stores confectioneries.

As product improvement is an on going process, we reserve the right to change specifications or design without notice.