

REFRIGERATED BARLINE 600/700 Series

Heated Glass , Frost Free • Tested at ambient temperature of 32°C



				2 Door		2 Door		2 Door		3 Door		4 Door	
MODEL	600 Series	B2D/C4/600-SM		B2D/C5/600-SM		B2D/C6/600-SM		B3D/C7/600-SM		B4D/C8/600-SM			
	700 Series	B2D/C4/7-SM		B2D/C5/7-SM		B2D/C6/7-SM		B3D/C7/7-SM		B4D/C8/7-SM			
Temperature°C		+1 to +6		+1 to +6		+1 to +6		+1 to +6		+1 to +6			
External Dim.(mm)		- 600 Series	1200 x (600 + 20) x 840	1500 x (600 + 20) x 840		1800 x (600 + 20) x 840		2100 x (600 + 20) x 840		2400 x (600 + 20) x 840			
		- 700 Series	1200 x (760 + 20) x 840	1500 x (760 + 20) x 840		1800 x (760 + 20) x 840		2100 x (760 + 20) x 840		2400 x (760 + 20) x 840			
Gross Volume (Litres)		- 600 Series	182	255		329		405		479			
		- 700 Series	263	366		472		576		681			
Voltage/ Frequency (V/ Hz)			230V/1/50HZ 220V/1/60HZ	230V/1/50HZ 220V/1/60HZ		230V/1/50HZ 220V/1/60HZ		230V/1/50HZ 220V/1/60HZ		230V/1/50HZ 220V/1/60HZ			
Cooling Capacity (W)			639	750		750		977		1316			
Wattage (W)		- 600 Series	326 - 361	440 - 486		402 - 444		511 - 565		558 - 616			
		- 700 Series	333 - 353	411 - 454		474 - 524		451 - 499		570 - 604			
Ampere (A)		- 600 Series	1.90 - 2.10	2.60 - 2.90		2.40 - 2.60		3.10 - 3.40		3.29 - 3.64			
		- 700 Series	1.94 - 2.06	2.40 - 2.70		2.70 - 3.0		2.90 - 3.20		3.37 - 3.57			
Refrigerant			R134a	R134a		R134a		R134a		R134a			
Defrost System			Forced Air Circulation	Forced Air Circulation		Forced Air Circulation		Forced Air Circulation		Forced Air Circulation			
PVC Coated Shelving			4	4		4		6		8			
Weight (kg)		- 600 Series	77	80.7		89.8		110.3		125.6			
		- 700 Series	97	107		117		143		158			
Unit For 20ft Container		- 600 Series	24	22		16		16		8			
		- 700 Series	22	22		14		14		8			
Unit For 40ft Container		- 600 Series	50	46		32		32		16			
		- 700 Series	46	42		28		28		16			

Note:

Option : CW - Castor Wheel / BF - Bullet Feet