

UPRIGHT CHILLER

Magnetic Solid Door • Tested at ambient temperature of 38°C



BS 2DUC/Z






BS 4DUC/Z





BS 6DUC/Z

Top View



Front View



2 Door

4 Door

6 Door

MODEL	BS 2DUC/Z	BS 4DUC/Z	BS 6DUC/Z
Temperature °C (celcius)	+1 to +6	+1 to +6	+1 to +6
External Dimension (mm)	650 x 770 x 2060	1300 x 770 x 2060	1950 x 770 x 2060
Gross Volume (Litres)	471	1029	1602
Voltage/Frequency (V/Hz)	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz
Cooling Capacity (W)	522	792	913
Wattage (W)	341 - 377	480 - 530	709 - 783
Ampere (A)	2.3 - 2.6	3.1 - 3.4	5.2 - 5.8
Refrigerant	R134a	R134a	R134a
Defrost System	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation
PVC Coated Shelving	4	8	12
Weight (kg)	97	147	201
Unit for 20ft Container	23	11	7
Unit for 40ft Container	48	23	15

Note:
Option : CW - Castor Wheel / BF - Bullet Feet