

UPRIGHT FREEZER

Magnetic Solid Door • Tested at ambient temperature of 38°C



BS 2DUF/Z





BS 4DUF/Z





BS 6DUF/Z

Top View



Front View



2 Door

4 Door

6 Door

MODEL	BS 2DUF/Z	BS 4DUF/Z	BS 6DUF/Z
Temperature °C (celcius)	-20 to -14	-20 to -14	-20 to -14
External Dimension (mm)	650 x 770 x 2060	1300 x 770 x 2060	1950 x 770 x 2060
Gross Volume (Litres)	471	1029	1602
Voltage/Frequency (V/Hz)	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz	230V/1/50Hz 220V/1/60Hz
Cooling Capacity (W)	680	876	1112
Wattage (W)	581 - 642	716 - 791	1238 - 1368
Ampere (A)	3.8 - 4.2	3.4 - 3.7	6.2 - 6.8
Refrigerant	R404a	R404a	R404a
Defrost System	Electric Heater	Electric Heater	Electric Heater
PVC Coated Shelving	4	8	12
Weight (kg)	102	165	228
Unit for 20ft Container	23	11	7
Unit for 40ft Container	48	23	15

Note:
Option : CW - Castor Wheel / BF - Bullet Feet