

V2 SPEECH DIALLERS

UNIVERSAL SPEECH DIALLERS

The V2 range of Speech Diallers enable communication of alarm information directly to telephone devices. Compatible with any brand of control panel via hardwired connection, they provide speech messages and SMS text messaging via a PSTN or GSM network.

KEY FEATURES

- ▶ 6 inputs onboard
- ▶ Up to 14 voice messages
- ▶ 9 telephone numbers
- ▶ Integrated microphone and speaker

V2GSM



V2TEL/PSTN



Specification features

	V2GSM	V2TEL/PSTN
Onboard / maximum inputs	6 expandable to 14	6
Onboard / maximum outputs	4 expandable to 52	4
Voice messages	Up to 14	6
SMS messages	Up to 14	x
Telephone numbers	9	9
Duplex	Full	Half
Integrated microphone and speaker	✓	✓
Integrated keypad	✓	✓
Remote control via a telephone	✓	✓
Automatic phone number recognition (CLIP)	✓	x
Can be used as a telephone	✓	✓
Date and time stamp	✓	x
Event log	256	30
Anti-jamming feature	✓	x

Other details

	V2GSM	V2TEL/PSTN
Operating temperature	-20°C to +40°C	-20°C to +40°C
Dimensions (W x H x D)	147 x 100 x 28mm	147 x 100 x 28mm
Power supply	10-14VDC	10-14VDC
Current consumption	300mA Max (40mA at rest)	300mA Max (40mA at rest)

Order information

SAP Code:	V2GSM	V2TEL/PSTN
International	361300137	361300140
France, North Africa, Switzerland	361300138	-
Germany, Austria, Switzerland	361300135	361300139
Italy, Switzerland	361300130	361300131
Russia, CIS	361300136	-
Spain, LATAM	361300166	-